

(4)

(18)

JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 08031465 A

(43) Date of publication of application: 02.02.98

(51) Int. Cl

H01M 12/08

(21) Application number: 08162885

(22) Date of filing: 18.07.94

(71) Applicant:

MATSUSHITA ELECTRIC IND CO LTD

(72) Inventor:


KUBO ISAO
NOYA SHIGETO
FUJIWARA TAKAFUMI
EDA NOBUO

(34) AIR DEPOLARIZED CELL

(57) Abstract:

PURPOSE: To prevent breakage of an air electrode, and improve safety and reliability by coating a positive electrode case of metal having air intake holes in a side part with a porous resin layer having air transmissive ability.

CONSTITUTION: An inner cup 6 of metal is inserted into a cylindrical air electrode 1 in which an outer cup of metal 5 is inserted at an upper part, a side surface of the outer cup 5 is compressed by a roller to form a groove 7 to be pressed to the air electrode 1, a cup side surface of the inner cup 6 is enlarged toward the air electrode 1 by an enlargement pin of a larger outer diameter than an inner diameter of the inner cup 6 for sealing, and a positive electrode case 8 of metal having a number of air intake holes 15 in a side surface can be provided. This positive electrode case 8 is coated with a porous resin



PATENT ABSTRACTS OF JAPAN

(11) Publication number: 10012288 A

(43) Date of publication of application: 16.01.98

(4)